

# 50

OUT OF SERVICE  
DO NOT  
OPERATE

THIS TAG MUST NOT  
BE REMOVED EXCEPT  
BY THE SIGNED OR  
AUTHORIZED  
PERSON.

OTHER SIDE

**30 Series**

RIVAFLEX 0.9N EN 88

HYDRA-FLUX

**FRONT JACKING / SUPPORT POINTS**  
**FRONT AXLE WEIGHT**

BY TRUCK ONLY, SEE WEIGHT ALLOWANCE  
+ MAXIMUM LOAD TIME TABLE  
LOCATION  
RED AREA IS RESTRICTED AREA

**REAR JACKING / SUPPORT POINTS**  
**REAR AXLE WEIGHT**

BY TRUCK ONLY, SEE WEIGHT ALLOWANCE  
+ MAXIMUM LOAD TIME TABLE  
LOCATION  
RED AREA IS RESTRICTED AREA

**NOTE:**  
FURTHER INFORMATION IS CONTAINED IN THE OPERATOR'S AND MAINTENANCE MANUAL FOR THIS MACHINE, LOCATED IN OPERATING POSITION.  
IT IS RECOMMENDED TO BE SUPPORTED UNASSISTED ON A FLOOR THAT HAS MORE THAN 1.5 INCHES OF CONCRETE OR EQUIVALENT STRENGTH. IN THIS CASE, CAPACITY OF EACH LEG IS 10,000 LBS.

**TRAC REFL. CAPACITIES**

Model	Capacity
50	1000
60	1500
70	2000
80	2500
90	3000
100	3500
110	4000
120	4500
130	5000
140	5500
150	6000
160	6500
170	7000
180	7500
190	8000
200	8500
210	9000
220	9500
230	10000
240	10500
250	11000
260	11500
270	12000
280	12500
290	13000
300	13500
310	14000
320	14500
330	15000
340	15500
350	16000
360	16500
370	17000
380	17500
390	18000
400	18500
410	19000
420	19500
430	20000
440	20500
450	21000
460	21500
470	22000
480	22500
490	23000
500	23500

